

RACK CABINETS

19" wall-mounted or floor-standing rack cabinet UNIRACK model

New
Design

New
Packaging

DESCRIPTION

The UNIRACK range with side doors for wall or floor installation is characterized by its elegant and versatile design, easily integrating into any environment. It is ideal for small data networks and is characterized by its load capacity, double set of depth-adjustable profiles, and cable entry with ABS plastic cover at the top and bottom.



APPLICATIONS

- IT, industrial, or telecommunications environments
- Wall or floor installation

OPENETICS
/ ADALTRA

Updated on: 10/15/2025

This document is confidential and the property of ADALTRA. ADALTRA owns the copyright and the document may not be copied or modified in any way, in whole or in part, without the written permission of ADALTRA. The features described in this document are not contractual and are subject to change without notice.

ADVANTAGES

- Ideal for small offices.
- Ready for forced ventilation installation.
- Cable entry with ABS plastic cover.
- Easy access to wiring through side doors.
- Double set of depth-adjustable profiles.
- Includes accessories for wall mounting (wall plugs and screws).
- Front and side accessibility.
- Tempered glass front door and metal side doors with quick-release fasteners.
- High load capacity.
- Full range of accessories available.
- Degree of protection: IP 20.
- Warranty: 5 years.

REGULATIONS

American standard for dimensions and mounting of 19" racks	EIA-310-D
Restriction of hazardous substances in electrical and electronic equipment	RoHS
Dimensions and mechanical compatibility of 19" racks and subracks	IEC 60297-2 / 60297-3
Compliance with European safety and quality directives	EC

TECHNICAL SPECIFICATIONS

Material	Cold-rolled steel UNE 36086-91
Color	Black RAL 9005
Maximum load	depending on the model
Height	from 310 mm to 1115 mm
Width	540 mm
Depth	450 mm and 600 mm
Frame height	6 U, 9 U, 12 U, 15 U, 20 U, and 25 U
Packaging unit	1
Front door	Lockable glass
Rear door	-
19" profiles	Adjustable depth
Side panels	Removable panels with quick-release fasteners
Cable entry	Superior and/or inferior
Wall mounting hardware	Included (anchors and screws)

COMMERCIAL INFORMATION

REFERENCE	COLOR	NO. U	STOP	WIDTH	PROF.	DOOR FORWARD	DOOR BACK
23234	Black RAL 9005	6 U	310	540	450	Glass	-
23235	Black RAL 9005	9 U	445	540	450	Glass	-
23236	Black RAL 9005	12 U	580	540	450	Glass	-
23237	Black RAL 9005	15 U	710	540	450	Glass	-
23231	Black RAL 9005	9 U	445	540	600	Glass	-
23232	Black RAL 9005	12 U	580	540	600	Glass	-
23233	Black RAL 9005	15 U	710	540	600	Glass	-
23224	Black RAL 9005	20 U	933	540	600	Glass	-
23225	Black RAL 9005	25 U	1155	540	600	Glass	-

OPTIONAL ACCESSORIES

REFERENCE	DESCRIPTION
23302/U	Set of 4 adjustable feet for UNIRACK (10 mm)
23301	Set of 4 wheels for UNIRACK
2545	130 m ³ /h fan for wall-mounted rack
23311	Silent 190 m ³ /h ventilation panel with thermostat for UNIRACK
27649	19" LED panel, 1U for rack lighting, 230 V, with switch
55300	19" WiFi unit for temperature control and alarms via EK Smart for Ref. 2545
2417	Removable 2U tray for keyboard (depth 300 mm)
2343	Fixed tray 1 U front mounting (depth 315 mm)
2344	Fixed tray 2 U front mounting (depth 315 mm)
2333	Fixed tray with 4 supports, 1U, for racks with a depth of 450 mm
2334	Fixed tray with 4 supports, 1U, for racks with a depth of 600 mm