
COAXIAL CABLE

CC 112 CA · CC 112 CA-250

- ✓ Screening Class A
- ✓ Inner conductor 1mm CCS
- ✓ Foil Al/PET/Al copper color
- ✓ Braiding 112 wires CCA



EKSELANS BY ITS



**CC 112 CA
CC 112 CA-250**



**Carton spool
CC 112 CA**



**Self-service
cardboard box
CC 112 CA-250**



TECHNICAL TABLE

REFERENCE		CC 112 CA	CC 112 CA-250
Code		151029	151030
Inner conductor	mm / Material	1 / CCS	1 / CCS
Dielectric	mm / Material	4,6 / PE	4,6 / PE
Foil	-	Al/PET/Al (copper plated)	Al/PET/Al (copper plated)
Mesh	Hilos / Material	112 / CCA	112 / CCA
Jacket	mm / Material	6,6 / PVC	6,6 / PVC
Shielding	dB	90	90
Class	-	A	A
Color	-	White	White
Attenuation	dB @ 50 MHz	4,7	4,7
	dB @ 100 MHz	6,4	6,4
	dB @ 230 MHz	9,1	9,1
	dB @ 470 MHz	13,2	13,2
	dB @ 862 MHz	17,9	17,9
	dB @ 950 MHz	19,1	19,1
	dB @ 1350 MHz	23,4	23,4
	dB @ 1750 MHz	26,7	26,7
	dB @ 2150 MHz	29,6	29,6
	dB @ 3000 MHz	33,9	33,9
Shielding	dB @ 5-1000 MHz	90	90
	dB @ 1000-2400 MHz	85	85
	dB @ 3000 MHz	75	75
Impedance	Ohm	75	75
Packaging	-	Carton Spool	Self-service cardboard box
Length	m	100	250