

COAXIAL CABLE

CC 112P · CC 112P-D



- ✓ CCS conductor
- ✓ Aluminium foil and mesh
- ✓ Cable for ICT 2. Annex II
- ✓ LSZH CPR Dca cover (CC 112P-D)



EKSELANS BY ITS



CC 112 P



**CC 112 P
CC 112 P-D**

TECHNICAL TABLE

REFERENCE		CC 112P	CC 112P-D
Code		151014	151028
Inner conductor	mm / Material	1 / CCS	1 / CCS
Dielectric	mm / Material	4,6 / PE	4,6 / PE
Foil	-	Al/PET/Al (Foil attached)	Al/PET/Al (Foil attached)
Mesh	Wires / Material	112 / Al	112 / Al
Jacket	mm / Material	6,6 PVC (Flame retardant)	6,6 LSZH
Reaction to fire	CPR	Eca	Dca s2 d2 a2
Shielding	dB	90	90
Class	-	A	A
Color	-	Blanco	Blanco
Attenuation	dB @ 50 MHz	4,7	4,7
	dB @ 100 MHz	6,4	6,4
	dB @ 230 MHz	9,1	9,1
	dB @ 470 MHz	13,2	13,2
	dB @ 862 MHz	17,9	17,9
	dB @ 950 MHz	19,1	19,1
	dB @ 1350 MHz	23,4	23,4
	dB @ 1750 MHz	26,7	26,7
	dB @ 2150 MHz	29,6	29,6
	dB @ 3000 MHz	33,9	33,9
Shielding	dB @ 5-1000 MHz	90	90
	dB @ 1000-2400 MHz	85	85
	dB @ 3000 MHz	75	75
Impedance	Ohm	75	75
Packaging	-	Carton Spool	Carton Spool
Length	m	100	100