



EKSELANS BY ITS

## COAXIAL CABLE CC 3S-100 / CC3S / CC 11T

Class A+ shielding

Trishield coaxial cable with CCS conductor and aluminium foil and mesh

Reference		CC 3S	CC 3S/100	CC 11T
Code		151004	151004	151015
Inner conductor	mm / Material	1,13 / CCS	1,13 / CCS	1,63 / CCS
Dielectric	mm / Material	4,6 / PE	4,6 / PE	7,24 / PE
Foil	-	Al/PET/Al x2 (Trishield)	Al/PET/Al x2 (Trishield)	Al/PET/Al x2 (Trishield)
Braid	Wires / Material	128 / Al	128 / Al	128 / Al
Jacket	mm / Material	6,9 / PVC	6,9 / PVC	10,3 / PE
Shielding	dB	110	110	110
	A	A+	A+	A+
Color	-	White	White	Black
Attenuation	dB @ 50 MHz	4,5	4,5	2,8
	dB @ 100 MHz	6,1	6,1	4,9
	dB @ 230 MHz	8,7	8,7	5,9
	dB @ 470 MHz	12,7	12,7	8,8
	dB @ 862 MHz	17,5	17,5	11,9
	dB @ 950 MHz	18,3	18,3	12,6
	dB @ 1350 MHz	22,5	22,5	15,6
	dB @ 1750 MHz	25,6	25,6	17,9
	dB @ 2150 MHz	28,5	28,5	19,8
	dB @ 3000 MHz	32,9	32,9	24
Shielding	dB @ 5-1000 MHz	110	110	110
	dB @ 1000-2400 MHz	100	100	100
	dB @ 3000 MHz	90	90	90
Impedance	Ohm	75	75	75
Packaging	-	Carton Pull Box	Carton Spool	Wooden drum
Length	m	250	100	300



CC 3S

CC 11T



BOBINA CC 11T



CAJA CC 3S