

COAXIAL CABLE

CC 3S · CC 11T

- √ Class A+ shielding
- √ Trishield coaxial cable with CCS conductor and aluminium foil and mesh
- √ CC 11T suitable for indoor and outdoor installations



EKSELANS BY ITS



CC 11T coil



CC 3S



CC 11T

TECHNICAL INFORMATION

REFERENCE		CC 3S	CC 11T
Code		151004	151015
Inner conductor	mm / Material	1,13 / CCS	1,63 / CCS
Dielectric	mm / Material	4,6 / PE	7,24 / PE
Foil	-	Al/PET/Al x2 (Trishield)	Al/PET/Al x2 (Trishield)
Braid	Hilos / Material	128 / Al	128 / Al
Jacket	mm / Material	6,9 / PVC flame retardant	10,3 / PE
Reaction to fire	CPR	Eca	-
Shielding	dB	110	110
Class	-	A+	A+
Color	-	White	Black
Attenuation	dB @ 50 MHz	4,5	2,8
	dB @ 100 MHz	6,1	4,9
	dB @ 230 MHz	8,7	5,9
	dB @ 470 MHz	12,7	8,8
	dB @ 862 MHz	17,5	11,9
	dB @ 950 MHz	18,3	12,6
	dB @ 1350 MHz	22,5	15,6
	dB @ 1750 MHz	25,6	17,9
	dB @ 2150 MHz	28,5	19,8
Shielding	dB @ 3000 MHz	32,9	24
	dB @ 5-1000 MHz	110	110
	dB @ 1000-2400 MHz	100	100
Shielding	dB @ 3000 MHz	90	90
Impedance	Ohm	75	75
Packaging	-	Carton Pull Box	Wooden coil
Length	m	250	300