

COAXIAL CABLES

CC 596 CU · CC 596 CUF

- ✓ Inner conductor in copper
- ✓ External sheath 5.1mm CPR Eca
- ✓ Class A shielding efficiency
- ✓ Two presentations: 100m and 150m



EKSELANS BY ITS



CC 596 CU · CC 596 CUF



**Carton reel 100m
CC 596 CU**



**Plastic film 150m
CC 596 CUF**



TECHNICAL INFORMATION

REFERENCE		CC 596 CU	CC 596 CUF
Code		151019	151035
Inner conductor	mm / Material	0,81 CU	
Dielectric	mm / Material	3,5 / PE	
Foil	-	AL/PET/AL	
Braid	Threads / Material	96 / AL	
Jacket	mm / Material	5,1 / PVC Eca	
Shielding	dB	90	
Class	-	A	
Color	-	Bianco	
Attenuation	dB @ 50 MHz	5,9	
	dB @ 200 MHz	11,3	
	dB @ 470 MHz	17,4	
	dB @ 800 MHz	23,3	
	dB @ 1000 MHz	26,5	
	dB @ 1350 MHz	30,5	
	dB @ 1750 MHz	35,8	
	dB @ 2150 MHz	40	
	dB @ 2400 MHz	42	
	dB @ 3000 MHz	49,9	
Shielding	dB @ 5-1000 MHz	90	
	dB @ 1000-2400 MHz	85	
	dB @ 3000 MHz	75	
Impedance	Ohm	75	
Packaging	-	Carton reel	Plastic film
Length	m	100	150