



EKSELANS BY ITS

COAXIAL CABLE

CC 96 / CC 96 N

Copper conductor with CCA foil and mesh

Physical dielectric (gas injected)

Reference		CC 96	CC 96 N
Code		151001	151016
Inner conductor	mm / Material	1 / Cu	1 / Cu
Dielectric	mm / Material	4,6 / PE	4,6 / PE
Foil	-	Al/PET/Al	Al/PET/Al
Braid	Wires / Material	96 / CCA	96 / CCA
Jacket	mm / Material	6,8 / PVC (Flame retardant)	6,8 / PVC (Flame retardant)
Shielding	dB	85	85
Class	A	A	A
Color	-	White	Black
Attenuation	dB @ 50 MHz	4,7	4,7
	dB @ 100 MHz	6,4	6,4
	dB @ 230 MHz	9,1	9,1
	dB @ 470 MHz	13,2	13,2
	dB @ 862 MHz	17,9	17,9
	dB @ 950 MHz	19,1	19,1
	dB @ 1350 MHz	23,4	23,4
	dB @ 1750 MHz	26,7	26,7
	dB @ 2150 MHz	29,6	29,6
	dB @ 3000 MHz	33,9	33,9
Shielding	dB @ 5-1000 MHz	85	85
	dB @ 1000-2400 MHz	80	80
	dB @ 3000 MHz	70	70
Impedance	Ohm	75	75
Packaging	-	Cartoon spool with reinforced metallic cilinder	
Length	m	100	100

