

COAXIAL CABLE

CC 96+ D · CC 96+D/250

CPR
Dca



- ✓ Cable for ICT 2.
Copper conductor
- ✓ CCA mesh
- ✓ Physical dielectric (gas injected)

Ek

EKSELANS BY ITS



CC 96+ D

TECHNICAL TABLE

REFERENCE		CC 96+D	CC 96+D /250
Code		151026	151027
Inner conductor	mm / Material	1.13 / Cu	1.13 / Cu
Dielectric	mm / Material	4,6 / PE	4,6 / PE
Foil	-	Copper + Polyester	Copper + Polyester
Mesh	Wires / Material	96 / CCA	96 / CCA
Jacket	mm / Material	6,8 LSZH	6,8 LSZH
Reaction to fire	CPR	Dca s2 d2 a2	Dca s2 d2 a2
Shielding	dB	85	85
Class	-	A	A
Color	-	White	White
Attenuation	dB @ 50 MHz	4,2	4,2
	dB @ 100 MHz	5,9	5,9
	dB @ 230 MHz	8,5	8,5
	dB @ 470 MHz	12,4	12,4
	dB @ 862 MHz	17,3	17,3
	dB @ 950 MHz	18,2	18,2
	dB @ 1350 MHz	22,4	22,4
	dB @ 1750 MHz	25,3	25,3
	dB @ 2150 MHz	28,3	28,3
	dB @ 3000 MHz	32,6	32,6
Shielding	dB @ 5-1000 MHz	90	90
	dB @ 1000-2400 MHz	85	85
	dB @ 3000 MHz	75	75
Impedance	Ohm	75	75
Packaging	-	Carton Spool	Self-service cardboard box
Length	m	100	250