ADALTRA

CLUR 6N CCA - 390028


CAT6 U/UTP CCA PE black CPR Fca LAN cable





DESCRIPTION

CAT6 U/UTP CCA PE black CPR Fca LAN cable, 305m reel for EK ROLLER



KEY FEATURES

4 twisted pairs with cross separator (spline) CPR Class Fca 305 m reel Compatible with EK ROLLER



Updated on: 20/10/25



FEATURES

REFERENCE	CLUR 6N CCA						
Code	390028						
CONSTRUCTION							
Shielding	U/UTP						
Conductor material	CCA						
Conductor diameter	23 AWG (0.57±0.005mm)						
Insulation material	HDPE						
Insulation nominal thickness	0.21mm						
Diameter	0.93±0.05mm						
Outer sheath material	PVC-FR						
Outer diameter	6,10±0.3mm						
Colour	Black						
Cross separator	Yes						
Ripcord	Yes						
ELECTRICAL CHARACTERISTICS							
Frequency range	1-250MHz						
Impedance	100±15Ω						
Nominal mutual capacitance	≤56nF/Km						
Maximum capacitance unbalance	≤330pF/100m						
Maximum DC resistance unbalance	≤9,5Ω/100m						
Jacket insulation withstand voltage	1KV						
GEN	ERAL						
Minimum bend radius	30mm						
Storage temperature range	-20°C ~ 80°C						
Installation temperature range	-20°C ~ 80°C						
Operating temperature	-20°C ~ 80°C						
Maximum tensile strength	100N						
CPR	Fca						
PACK	AGING						
305 m wooden reel, compatible with EK ROLLER							
WEIGHT							
Kg	11,5 / 9.7						
COLOUR CODE							
Pair1	Blue – white/blue						
Pair2	Orange – white/orange						
Pair3	Green – white/green						
Pair4	Brown - white/brown						



Frequency (MHZ)	Max. Att (dB/100m)	NEXT (dB)	RL (dB)	PS-NEXT (dB)	ELFEXT (dB)	PSELFEXT (dB)
1	2.0	74.3	20.0	72.3	67.8	64.8
4	3.8	65.3	23.0	63.3	55.8	52.8
8	5.3	60.8	24.5	58.8	49.7	46.7
10	6.0	59.3	25.0	57.3	47.8	44.8
16	7.6	56.2	25.0	54.2	43.7	40.7
20	8.5	54.8	25.0	52.8	41.8	38.8
25	9.5	53.3	24.3	51.3	39.8	36.8
31.25	10.7	51.9	23.6	49.9	37.9	34.9
62.5	15.4	47.4	21.5	45.4	31.9	28.9
100	19.8	44.3	20.1	42.3	27,8	24.8
200	29.0	39.8	18.0	37.8	21.8	18.8
250	32.8	38.3	17.3	36.3	19.8	16.8



ADDITIONAL INFORMATION

Ek R©LLER

EK ROLLER is a patented cable dispenser concept by EK that offers unique advantages in the market. Its low weight and compact size let you store it in a toolbox, making it easy to handle in any situation or environment. Thanks to its robust steel frame, it supports both lightweight reels under 1 kg and reels over 30 kg.

- The quick-mount system attaches to the reel in just two seconds, allowing fast, tool-free reel changes. Once attached, it is automatically integrated with EK's exclusive reels with handle, further improving ease of use and portability.
- EK ROLLER not only enables smooth cable unwinding by simply pulling the cable, but also
 makes the tedious task of rewinding leftover cable at the end of an installation quick and
 comfortable.
- EK reels compatible with EK ROLLER also feature an innovative system that prevents leftover cable loops from tangling, ensuring consistently smooth unwinding.



Updated on: 20/10/25