

TRANSMODULATION HEADEND UNIVERSAL INPUT TO IP MULTICAST CM 3STC-IP / CM 3STC CI-IP



TRIPLE Universal module. Up to 2x DVB-S/S2/T/T2/C input transponders / muxes
Independent control of each tuner 13V/18V – 22 KHz – DiSEqC (A/B/C/D)
Pass-through or supression of EMM / CAT tables
100 Mbps SPTS/MPTS IP output with UDP/RTP
Flexible remultiplexation of IP output services
SAP Function
Up to 16 output streams
Programming via Software PC "CM Management"
Configuration cloning and report
Remote control integrated in the FA 524 source using CM KEY

REFERENCE		CM 3STC-IP	CM 3STC CI-IP
Code		082033	082030
INPUT			
Number of tuners		3 (A, B, C)	3 (A, B, C)
Input connectors		3 SAT + 3 TER/CAB	3 SAT + 3 TER/CAB
Reception DVB-S/S2			
Input frequency	MHz	950 - 2150	
Input level	dBµV	43-83	
Modulation		QPSK / 8PSK	
Symbol rate	MSps	1 - 45	
Remote feeding	Vdc / KHz	13-18 / 0-22	
Diseqc		A / B / C / D	
Reception DVB-T/T2			
Input frequency	MHz	110 - 862	
Input level	dBµV	33-88	
Constellation - Mode		QPSK, 16, 64, 256QAM 1K, 2K, 4K, 8K, 16K, 32K	
Reception DVB-C			
Input frequency	MHz	110 - 862	
Input level	dBµV	46 - 88	
Constellation - Mode	-	QPSK, 16, 32, 64, 128, 256QAM 6, 7, 8	
Symbol rate	MSps	0,2 - 7,7	
COMMON INTERFACE			
Slots		-	1
OUTPUT			
Connector		RJ45 - Fast Ethernet	
Routing scheme		Unicast / Multicast	
Maximum services		16 (SPTS / MPTS)	
Protocols		UDP / RTP / QoS / SAP	
GENERAL			
Local Programming		USB / RJ45 (LAN)	
Remote programming		RJ45 (Internet) + CM Key	
Feeding	Vdc	5	



CM 3STC-IP



CM 3STC CI-IP