

CABECERA CM

CM 4AV-IP • CM 4HD-IP



- ✓ Modules QUAD to IP multicast
- ✓ Adjustment of coding parameters
- ✓ 100 Mbps SPTS/MPTS IP output with UDP/ RTP
- ✓ Flexible remultiplexation of IP output services
- ✓ SAP Function
- ✓ Up to 16 output streams
- ✓ Programming via Software PC "CM Management"
- ✓ Configuration cloning and reports
- ✓ Remote control integrated in the FA 524 source using CM KEY



EKSELANS BY ITS



CM 4AV-IP



CM 4HD-IP

TECHNICAL TABLE

REFERENCE		CM 4AV-IP	CM 4HD-IP
Code		082007	082008
Input			
Number of inputs		4 (A1, B1, A2, B2)	4 (A, B, C, D)
A/V			
Video		CVBS	-
Input level	Vpp	0,7 - 1,4	-
Impedance	Ω	75	-
Video compression		MPEG2	-
Video bitrate	Mbps	4 - 12	H.264 / 5 - 15
Audio compression		MPEG1 Layer 2	-
Audio bitrate	Kbps	128 - 384	AAC-LC, MPEG1-L2 / 128 - 384
HDMI			
Maximum		576p	1080p
Output			
Connector		RJ45 - Fast Ethernet	
Routing scheme		Unicast / Multicast	
Maximum services		16 (SPTS / MPTS)	
Protocols		UDP / RTP / QoS / SAP	
GENERAL			
Local Programming		Cable USB / RJ45 (LAN)	
Remote programming		RJ45 (Internet) (CM Key)	
Feeding	Vdc	5	
Consumption	mA	2000	2400
Operating temperature	°C	0 - 40	