

CM HEADEND

CM 8SH CI-TC



- ✓ OCTO module with 4 SAT inputs and 8 tuners
- ✓ 1 HDMI input
- ✓ 1 USB 2.0 input
- ✓ Independent control of each input 13 / 18V - 22KHz - DiSEqC (A / B / C / D)
- ✓ Flexible remultiplexing of services on any output channel
- ✓ Editing NIT tables, SID remapping and passing or deleting EMM messages and CAT tables
- ✓ Programmable QAM / COFDM output
- ✓ Output of up to 4 channels COFDM / 4 flexible QAM channels
- ✓ High output level
- ✓ Excellent output signal quality with a high MER
- ✓ LCN / LCN HD insert
- ✓ Programming via SW PC ("CM Management")
- ✓ Configuration cloning and reporting
- ✓ On-site management (FA 510 / CM PR) or remote (FA 524)
- ✓ 2 common interface slots



EKSELANS BY ITS



CM 8SH CI-TC



TECHNICAL INFORMATION

REFERENCE		CM 8SH CI-TC
Code		082256
INPUT		
Number of inputs		4x RF + 1x HDMI + 1x USB
Number of tuners		8
Input frequency	MHz	950 - 2150
Input level	dBμV	40 - 79
Symbol rate	Mbps	1 - 45
Modulation type		QPSK / 8PSK / 16APSK / 32APSK
Telepower	V / KHz	13/18 - 0/22
Common interface		2 x CI
DiSEqC		A / B / C / D
USB		
Priority		1
Version		2.0
File System		FAT32 / NTFS
Reproduction		Autoplay, List, Time schedule
File format		.TS (Transport Stream)
HDMI		
Priority		2
Video / Bitrate	- / Mbps	H.264 / 5 - 15
Audio / Bitrate	- / Kbps	AAC-LC, MPEG1-L2 / 128 - 384
Max resolution		1080p
OUTPUT		
Number of outputs		1
Mixing port	dB	<1,5
Output frequencies	MHz	170 - 862
Maximum output level	dBμV	95
Output regulation	dB	20
DVB-T modulation		
Number of channels		4 flexible
Output frequency	MHz	170 - 230 / 470 - 862
Constellation - Mode		QPSK, 16QAM, 64QAM - 2K
Bandwidth	MHz	7 y 8
FEC		1/2, 2/3, 3/4, 5/6, 7/8
Guard interval		1/4, 1/8, 1/16, 1/32
MER	dB	>32
DVB-C modulation		
Number of channels		4 flexible
Output frequency	MHz	170 - 230 / 470 - 862
Constellation		16, 32, 64, 128, 256QAM
Bandwidth	MHz	7 y 8
Symbol rate	MSps	4 .. 6,96
MER	dB	>32
GENERAL		
Local programming		By USB / RJ45 cable (LAN) with FA 524 or CM PR
Remote programming		By RJ45 (Internet) (CM Key)
Power supply	Vdc	5
Consumption (No LNB, no USB, no CAM, no HDMI)	mA	4300
Operating temperature	°C	0 - 40

- Specifications and design are subject to change without notice

- The product meets the requirements of the CE marking. The declaration of conformity is available on the website www.ek.plus