

CM HEADEND

CM IP CI-IP



- ✓ Input up to 31 IP Unicast / Multicast services
- ✓ Supported protocols: SPTS / MPTS, UDP / RTP, SIP, QoS
- ✓ Support services with different input bit rates
- ✓ 2 slots common interface
- ✓ IP output 1Gbps SPTS / MPTS in UDP / RTP format
- ✓ Up to 64 output streams
- ✓ SAP function
- ✓ IGMP Query and IGMP Auto-Joint
- ✓ Programming via SW PC ("CM Management")
- ✓ Configuration cloning and reporting
- ✓ On-site management (FA 510 / CM PR) or remote (FA 524) using CM KEY



EKSELANS BY ITS



CM IP CI-IP

TECHNICAL INFORMATION

REFERENCE		CM IP CI-IP
Code		082037
INPUT		
Connector		RJ45 - Fast Ethernet
Routing scheme		Unicast / Multicast
Maximum streams		31 (SPTS / MPTS)
Supported protocols		IEEE 802.3, SPTS/MPTS, UDP, RTP, QoS
Local IP assignment		DHCP / Static
PCR (Program Clock Reference)		Acorde con ETSI TR 101 290
COMMON INTERFACE		
Slots		2
OUTPUT		
Connector		RJ45 - Fast Ethernet
Routing scheme		Unicast / Multicast
Maximum streams		64 (SPTS / MPTS)
Protocols		UDP / RTP / QoS / SAP
Features		IGMP Query e IGMP Auto-Joint
GENERAL		
Local programming		By USB / RJ45 cable (LAN) with FA 524 or CM PR
Remote programming		By RJ45 (Internet) (CM Key)
Power supply	Vdc	5
Consumption (no CAM)	mA	1300
Operating temperature	°C	0 - 40