

WIRELESS OUTDOOR CPE / AP

CPE 1200-OLP



- ✓ High-speed 802.11AC 1200 Mbps
- ✓ 2.4 GHz and 5.8 GHz frequency bands
- ✓ Supports high user density
- ✓ Multiple SSID
- ✓ Portée 400m (*)
- ✓ AP Mode / Router / Repeater / WISP
- ✓ PoE 48Vdc power supply



EKSELANS BY ITS



CPE 1200-OLP



Schéma d'installation:



TECHNICAL TABLE

REFERENCE	CPE 1200-OLP
Code	333009
Hardware	
Antenne	4 x Omni 5 dBi
Puissance de transmission	Max. 24 - 27 dBm (IEEE802.11 b/g/n) - 2.4Ghz Max. 21 -24 dBm (IEEE802.11 n/ac) - 5.8Ghz (EK recommande le réglage de la puissance d'émission maximale conformément à la réglementation en vigueur dans chaque pays)
Bouton de réinitialisation	Reset et réglages d'usine
Logiciel	
Programmation	Network management WEB et contrôleur
Options	VLAN, QoS, bandwidth control, limitation "broadcast storm",...
Connexions	
Interface Ethernet	2 x 10/100/1000 Mbps Ethernet ports
Alimentation	PoE: 48V ; 12 Vdc/2A
Spécifications Wireless	
Mode de travail	AP, Gateway, Repeater
Throughput 2.4 GHz	IEEE802.11B: 11MBPS IEEE802.11G: 54MBPS IEEE802.11N: 300MBPS
Throughput 5.8 GHz	IEEE802.11ac: 900Mbps
Fréquence	2.4 GHz
	5.180 GHz-5.825 GHz
Canal	36 - 165
Modulation	OFDM
Codification	BPSK, QPSK, 16QAM and 64QAM
Cryptage	802.11i Security: WEP-64/128, TKIP(WPA-PSK) and AES(WPA2-PSK)
Général	
Température de fonctionnement	-40°C - 70°C
Consommation	Max. 10 W
Dimensions	31,5 x 14,5 x 8 cm

(*) La distance maximale dépend des conditions d'utilisation du point d'accès