



EKSELANS BY ITS

DERIVATORI CON CONNETTORI F DF 2XX / DF 4XX / DF 8XX

Efficienza di schermatura classe A
Passaggio DC sulla linea principale
5-2300 MHz

ARTICOLO		DF 212	DF 216	DF 220	DF 224	DF 412	DF 416	DF 420	DF 424	DF 816	DF 820	DF 824
Codice		142001	142002	142003	142004	142005	142006	142007	142008	142009	142010	142011
Banda passante	MHz	5-2400	5-2400	5-2400	5-2400	5-2400	5-2400	5-2400	5-2400	5-2400	5-2400	5-2400
Uscite	N°	2	2	2	2	4	4	4	4	8	8	8
Attenuazione di derivazione	dB (+/-1)	12	16	20	24	12	16	20	24	16	20	24
Perdite di passaggio	dB 860 MHz	<2,2	<1,6	<1,1	<1	<3,2	<1,8	<1,5	<1,3	<3,8	<1,9	<1,4
	dB 2300 MHz	<3,5	<2,6	<2,6	<2,3	<4,5	<3,5	<2,1	<2	<4,9	<3,2	<2,1
Isolamento tra uscite	dB	>20	>20	>20	>20	>20	>20	>20	>20	>20	>20	>20
Perdite di ritorno	dB	>10	>10	>10	>10	>10	>10	>10	>10	>10	>10	>10
Passaggio DC	mA	500	500	500	500	500	500	500	500	500	500	500



DF 2XX



DF 4XX



DF 8XX