



EKSELANS BY ITS

TAPS



DQCF 412 · DQCF 416
DQCF 420 · DQCF 424

- ✓ 4 Output
- ✓ Low insertion loss
- ✓ DC pass in trunk line



DQCF 424



NOW WITH **F CONNECTOR**
ALREADY INSERTED



ALL REFERENCES
INCLUDE
F CONNECTORS
ALREADY INSERTED



TAPS WITH **ALL**
CONNECTORS ON
SAME SIDE



YOU CAN **CONVERT**
THEM TO QUICOAX
BY REMOVING THE
F CONNECTORS AND
THUS ENJOY ALL ITS
ADVANTAGES

TECHNICAL TABLE

REFERENCE	DQCF 412	DQCF 416	DQCF 420	DQCF 424
CODE	142038	142039	142040	142041
LOSS				
Insertion loss (in-out) 5-47 MHz	<3 dB	<2.5 dB	<1.3 dB	<0.5 dB
Insertion loss (in-out) 47-950 Mhz	<4.1 dB	<2.6 dB	<1.6 dB	<0.8 dB
Insertion loss (in-out) 950-2150 MHz	<4.5 dB	<3.2 dB	<2.5 dB	<1.5 dB
Insertion loss (in-out) 2150-2400 Mhz	<4.7 dB	<3.6 dB	<3.1 dB	<2.2 dB
Tap loss (in-tap) 5-47 MHz	12 dB ±1.5 dB	16 dB ±1.5 dB	20 dB ±1.5 dB	24 dB ±1.5 dB
Tap loss (in-tap) 47-950 Mhz	12 dB ±1.5 dB	16 dB ±1.5 dB	20 dB ±1.5 dB	24 dB ±1.5 dB
Tap loss (in-tap) 950-2150 MHz	12 dB ±1.5 dB	16 dB ±1.5 dB	20 dB ±1.5 dB	24 dB ±1.5 dB
Tap loss (in-tap) 2150-2400 Mhz	12 dB ±1.5 dB	16 dB ±1.5 dB	20 dB ±1.5 dB	24 dB ±1.5 dB
ISOLATION				
Isolation (tap-tap) 5-47 MHz	>25 dB	>25 dB	>25 dB	>25 dB
Isolation (tap-tap) 47-950 MHz	>30 dB	>22 dB	>23 dB	>25 dB
Isolation (tap-tap) 950-2150 MHz	>26 dB	>20 dB	>23 dB	>25 dB
Isolation (tap-tap) 2150-2400 MHz	>22 dB	>20 dB	>25 dB	>28 dB
Isolation (tap-out) 5-47 MHz	>35 dB	>23 dB	>35 dB	>35 dB
Isolation (tap-out) 47-950 MHz	>30 dB	>23 dB	>30 dB	>30 dB
Isolation (tap-out) 950-2150 MHz	>32 dB	>24 dB	>24 dB	>30 dB
Isolation (tap-out) 2150-2400 MHz	>32 dB	>25 dB	>24 dB	>28 dB
RETURN LOSS				
Return loss 5-47 MHz	>12 dB	>15 dB	>15 dB	>15 dB
Return loss 47-950 MHz	>14 dB	>15 dB	>15 dB	>15 dB
Return loss 950-2150 MHz	>12 dB	>15 dB	>15 dB	>15 dB
Return loss 2150-2400 MHz	>12 dB	>12 dB	>12 dB	>12 dB
OPERATIONAL				
Impedance	75 Ω	75 Ω	75 Ω	75 Ω
Application	SAT, MATV 2.4Ghz +DC	SAT, MATV 2.4Ghz +DC	SAT, MATV 2.4Ghz +DC	SAT, MATV 2.4Ghz +DC
Screening Efficiency	EN50083-2 Class A +10dB	EN50083-2 Class A +10dB	EN50083-2 Class A +10dB	EN50083-2 Class A +10dB
DC Passthrough	Yes (max. 500mA)	Yes (max. 500mA)	Yes (max. 500mA)	Yes (max. 500mA)
Environment	Indoor	Indoor	Indoor	Indoor
CABLE CONNECTION				
Number of inputs	1	1	1	1
Number of outputs	1	1	1	1
Number of taps	4	4	4	4
Connection Type	F (QuiCoax option)			
MECHANICAL				
Product Depth	16 mm	16 mm	16 mm	16 mm
Product Height	38 mm	38 mm	38 mm	38 mm
Product Width	103 mm	103 mm	103 mm	103 mm
Packing QTY	1	1	1	1
Net Weight	0,114kg	0,114kg	0,114kg	0,114kg

Ekselans by ITS

Test of: Coupling transfer function (Ed.2)

Information for test

Test Job: 3000 Operator: J.M. Measurement: 05.02.2020 11:47:46
 Test set-up: triaxial cell 1000/150+TELASS 3000 A++
 Remark: triaxial cell 1000/150

Device under test

Item Number: 0000 Cable type: EK RQC 2-1 cell 1000/15
 Type: coaxial Zw: 75.0 Ohm
 Test length: 1.00 m Eps r: 1.5



Test parameter

Start frequency: 10.0 kHz Gen. Power: 0.0 dBm Add. parameter of transfer impedance:
 Stop frequency: 3.0 GHz Atten.(P1/P2): 0.0 dB Test-setup: Short-Matched
 Number of points: 801 R1(Z1): 75.0 Ohm
 Distance of points: log R2: 0.0 Ohm Eps r2: 0.0
 IF-BW: 10 Hz Rp: --- Z2: 0.0 Ohm
 Z(NWA): 50.0 Ohm Rs: --- lex: 0.0 m

Test diagram

Coupling transfer function (Ed.2) EK RQC 2-1 cell 1000/15

