
INTERNET OVER COAX

IPC-S3



- ✓ IP reception signal via coaxial cable
- ✓ Working bandwidth 7,5-65 MHz
- ✓ 4 ports LAN 10/100 + Router Wifi
- ✓ VLAN Configuration
- ✓ With IPTV management for indoor WiFi extension

**IPCM2
COMPATIBLE**



IPC-S3

TECHNICAL INFORMATION

REFERENCE	IPC-S3
Código	250024
Operating characteristics	
RF parameters	
Frequency	7.5–65MHz
Output level	110 dBuV
Minimum input level	45 dBuV
Return loss	> 15 dB
Transmission speed	
Operating mode	TDMA / CSMA
Encryption	AES-128
Standards	
EOC Standard	IEEE P1901 HomePlug AV
Ethernet protocols	IEEE802.3, IEEE802.3x, IEEE802.3u, IEEE802.1P, IEEE802.1Q
Software	
Manner of use	Network management WEB, CLI and SNMP
Software characteristics	VLAN, QoS, bandwidth control, limitation "broadcast storm", ...
Connections	
RF Connection	1 RF IN (connector F) 1 RF OUT (connector F)
Ethernet Interface	4 10/100M Ethernet (connectors RJ45) ports
Power Supply	DC12Vdc Connector
Consumption	< 5W
Wi-Fi Characteristics	
Operating mode	Router or Bridge
Antenna	2 x Antennas 2.4 Ghz
Throughput	IEEE802.11b: 11Mbps IEEE802.11g: 54Mbps IEEE802.11n: 300Mbps
Frequency	2.412GHz–2.472GHz
Channel	13. Configurable for various standards
Modulation mode	DSSS, CCK and OFDM
Coding	BPSK, QPSK, 16QAM and 64QAM
Encryption	802.11i Security: WEP-64/128, TKIP(WPA-PSK) and AES(WPA2-PSK)