

2-WIRE SINGLE-FAMILY VIDEO DOOR KITS

VIDEK HOME WIFI

Kit with:

PE 1BM: Outdoor panel

+ **MON 43W:** Touchscreen monitor 4,3" WiFi

PFA 2420: Power supply

- ✓ Single-Family Video Door Kit
- ✓ Installation with 2 non-polarized wires
- ✓ Outdoor panel with camera, push button, and Mifare access control
- ✓ Hands-free 4.3-inch color touchscreen monitor with wall-mount support
- ✓ Wi-Fi Connection for Call Forwarding and Remote Door Opening via Smartphone using the EK SMART App
- ✓ DIN rail installation power supply
- ✓ Expandable up to 4 monitors and 2 outdoor panels
- ✓ Call recording via SD card (not included)
- ✓ Automatic opening system through time settings (professional offices, stores, medical centers, etc.)
- ✓ Do not disturb mode
- ✓ Voicemail system



EKSELANS BY ITS



VIDEK HOME WIFI



Download



PE 1BM
321013



MON 43W
320005



PFA 2420
323002



Call Forwarding and Remote Door Opening via Smartphone

TECHNICAL INFORMATION

REFERENCE	VIDEK HOME WIFI	
Code	322004	
REFERENCE		PE 1BM
Voice volume adjustment		Yes
Monitoring time	s	20
Time speaks	s	20
Terminals		BUS, BUS
Supply voltage	V	24
Consumption (Standby)	mA	30
Consumption (Work)	mA	95
Work temperature	°C	-10 ~ +40
Humedad relativa de trabajo	% Hum	10 ~ 90
REFERENCE		MON 43W
Screen format	Ratio / "	16:9 / 4,3
Screen size	mm	95 x 54
Screen resolution	Pixels	480 x 272
Pixel size	mm	0,10 x 0,37
Tone volume adjustment		Yes
Speaker volume adjustment		Yes
Brightness adjustment		Yes
Contrast adjustment		Yes
Monitoring time	s	~45
Speaking time	s	~45
Terminals		BUS, BUS
Voltage feeding	Vdc	24
Consumption (Standby)	mA	130
Consumption (Working)	mA	220
Temperatura de trabajo	°C	-10 ~ +40
Humedad relativa de trabajo	% Hum	10 ~ 90
REFERENCE		PFA 2420
Input voltage	Vac / Hz	100-240 / 50-60
Output voltage	Vdc	24
Maximum output current	A	2
Maximum power	W	48
Primary electrical terminals		L, N, GND
Secondary electrical terminals		4 x BUS
Fixing		DIN Rail (7 modules) / Wall
Working temperature	°C	-10 / +40
Working humidity range	% Hum	10 / 90