

## RFID CARD ACCESS CONTROL SYSTEM CCA / LCA

Controller CCA may be fed with a wide range of AC or DC voltage

Compatible with various types of lock (AC / DC)

Anti-vandal and water resistant card reader LCA (IP66). Fed from controller

Adjustable opening time (1-99s)

Expandable system through other controllers (door access)

Manual or remote programming (Through remote control)

Compatible with existing installations

| REFERENCE                               |          | CCA          |
|-----------------------------------------|----------|--------------|
| Code                                    |          | 370001       |
| Maximum number of users                 |          | <1000        |
| Transmission protocol reader-controller |          | Wiegand      |
| Working voltage / Nominal               |          |              |
| AC                                      | V (rms)  | 12~30 / (24) |
| DC                                      | Vdc      | 9~24 / (12)  |
| Consumption (Standby /Maximum)          |          |              |
| AC                                      | mA (rms) | 115 / 170    |
| DC                                      | mA       | 60 / 80      |
| Lock maximum consumption                | A        | 2            |
| Maximum distance IR sensor - Keyboard   | m        | <10          |
| Working temperature                     | °C       | -40 ~ 60     |
| Working condition humidity              | % Hum    | 0 ~ 90       |
| Dimensions                              | mm       | 90 x 63 x 22 |

| REFERENCE             |     | LCA           |
|-----------------------|-----|---------------|
| Code                  |     | 370002        |
| Card type             |     | Mifare        |
| Frequency             | MHz | 13,56         |
| Reading range         | cm  | 3             |
| Output protocol       |     | Wiegand 34b   |
| Mains voltage         | Vdc | 9~24          |
| Consumption (Standby) | mA  | 25            |
| Protection index      |     | IP66          |
| Working temperature   | °C  | -40 ~ 60      |
| Dimensions            | mm  | 103 x 48 x 19 |

| REFERENCE  |     | RF KEY |
|------------|-----|--------|
| Code       |     | 371001 |
| Frequency  | MHz | 13,56  |
| Technology |     | Mifare |
| Quantity   | PCS | 5      |



CCA



LCA



RF KEY