



EKSELANS BY ITS

MODULATORI / ENCODER COFDM SD MD SD

Excellent quality of modulation MER \geq 35dB

ARTICOLO		MD SD
Codice		122003
Ingressi video	Ingresso	CVBS
	Modo risoluzione	PAL (720x576 / NTSC /720x480)
	Compressione	MPEG 2
Ingressi audio	Ingresso	Audio estéreo x 2/ 0,5-2,5 Vpp
	Sample rate	48 KHz
	Compressione	MPEG1,LAYER II
DVB	Inserzione tabella	PAT, PNT, SDT, NIT
	Configurazione	Program name, SID, LCN, NETWORK NAME, TSD, ONID, NID, VERSION NIT, LCN, PID, PMT, PID VIDEO, PID AUDIO
Uscita DVB-T	Frequenza di uscita / livello	47-862 MHz / >80 dB μ V. ADJUSTABLE 0-29 dB
	Constellazione – FEC	QPSK/16QAM/64QAM - 1/2, 2/3, 3/4, 5/6, 7/8
	Intervallo di guardia	1/4, 1/8, 1/16, 1/32
Alimentazione	MER	2K/8K - 35 dB
	Connettore DC 2.1 mm	+5V
	Assorbimento	10 Watts
Dimensioni	Lungo x Largo x Alto	170 x 130 x 35 mm
	Peso	0,6 kg



MD SD



CSR



CHD

CODICE	ARTICOLO	DESCRIZIONE
123001	CSR	Cable Scart / 3 x RCA
125001	CHD	Cale HDMI / HDMI 1,5 m
123002	CRR	Cavo 3 x RCA / 3 x RCA 1,5m