

MINIMCD-1G-P60SFP - 314003



Mini industrial media converter
10/100/1000 to 100/1000 Base-X SFP,
POE output 60W

DESCRIPTION

Mini industrial media converter 10/100/1000 to 100/1000 Base-X SFP, POE output 60W. Power supply not included



KEY STRENGTHS

- 1-port 10/100/1000BASE-T RJ45 with auto MDI / MDI-X function
- 1 SFP Port, 100Base-FX or 1000Base-X dual mode (auto detection)
- IEEE802.3af/at compliant
- Up to 60W of power over 4-pairs
- IEEE 802.3az Energy Efficient Ethernet (EEE) compliant
- Supports Full/Half-duplex, Auto-negotiation
- 12~48VDC Terminal Block Power Input
- Supports DIN-Rail & Wall-mount installation
- Environmentally hardened -40°C to 75°C (-40°F to 167°F) operating temperature



Updated on: 3 December 2025

This document is confidential and the property of ADALTRA. ADALTRA holds the copyright, and the document may not be copied or modified, in whole or in part, in any form, without ADALTRA's prior written permission. The features/specifications indicated in this document are non-contractual and may be changed without prior notice.

SPECIFICATIONS

REFERENCE	MINIMCD-1G-P60SFP
Code	314003
ETHERNET	
Standards:	IEEE802.3 10Base-T IEEE802.3u 100Base-TX/FX IEEE802.3ab 1000Base-T IEEE802.3z 1000Base-X IEEE 802.3az Energy Efficient Ethernet (EEE) IEEE802.3af Power over Ethernet IEEE802.3at Power over Ethernet
Processing Type:	Store-and-Forward
Forward Filter Rate:	14,880pps (10Mbps)
	148,800pps (100Mbps)
	1,488,000pps (1000Mbps)
Packet Buffer Memory:	1 Mbit
Max Packet Length:	9K Bytes
Address Table Size	2048K MAC Addresses
INTERFACE	
Connector:	1x RJ45
Optical Port:	1 x SFP 1000Base-X or 100Base-FX (auto detection)
ELECTRICAL AND MECHANICAL	
Input Power:	12~48VDC, 2-pin terminal block
Power Consumption:	65W Max.
LED INDICATORS:	
PWR:	Power Status
PoE:	PD Plug Status
RJ45:	LINK/Activity
SFP:	LINK
Dimensions (WxDxH):	95 x 70 x 30 mm
Weight:	0.25Kg
Casing:	Aluminum Case
Mounting Options:	DIN-Rail / Wall-mount
ENVIRONMENTAL	
Operating Temperature:	-40°C to 75°C (-40°F to 167°F)
Storage Temperature:	-40°C to 85°C (-40°F to 185°F)
Relative Humidity:	5% to 95% non-condensing
MTBF	> 200,000 hrs