

USER MANUAL

MU CAST 280098

Universal remote control setup for TV, CAST device (CRP 4K)

V03



INDEX

INTRODUCTION:	3
Packaging Contents:	3
SETTING UP THE REMOTE CONTROL:	4
CLONING PROCESS:	8
MANAGEMENT OF CLONED CONFIGURATIONS:	10
NOTE:	11
Pairing with CRP 4K:	11
STB Prof Linkage:	12



INTRODUCTION:

The MU CAST direct app allows users to set up and/or clone remote controls connected to their mobile devices. This manual guides you through the process of configuring/cloning a remote control, from accessing the feature to managing the cloned configurations.

Packaging Contents:

- 1. Remote control
- 2. 2 AAA batteries



SETTING UP THE REMOTE CONTROL:

Download the app from the Google Play Store or the Apple App Store. Install the following App on a device with Bluetooth activated and an Internet connection.

Google Play Store		App Store Apple
	Open the app and press control until the LED flas	s OK on the remote shes.
	The remote will connect	with the phone.

Ek ekselans by its





942 2	We will choose the brand of the TV so t the different remote control codes related the chosen manufacturer are downloade
Samsung 🗸	
LG	
Sony	
Toshiba	
TCL	
Sharp	
Panasonic	
Hisense	
Sanyo	
Philips	
Α	
۲۲۲ (۲۲۵ (۲۲۵ (۲۲۵ (۲۲۵ (۲۲۵ (۲۲۵ (۲۲۵	Once the TV has been selected, differe remote control configurations will be load sequentially. The App will ask you to try a key to see if i
x22 & R N I I I I I I I I I I I I I I I I I I	Once the TV has been selected, difference remote control configurations will be load sequentially. The App will ask you to try a key to see if i the correct one. If not, another configuration will be loaded until the correct one is four
vert we	Once the TV has been selected, differer remote control configurations will be load sequentially. The App will ask you to try a key to see if in the correct one. If not, another configurati will be loaded until the correct one is four
922 # • • • • • • • • • • • • • • • • • •	Once the TV has been selected, differer remote control configurations will be load sequentially. The App will ask you to try a key to see if i the correct one. If not, another configurati will be loaded until the correct one is four
922 * • • • • • • • • • • • • • • • • • •	Once the TV has been selected, differer remote control configurations will be load sequentially. The App will ask you to try a key to see if i the correct one. If not, another configurati will be loaded until the correct one is four





Samsung Samsung Understand yes, it works	
no, try again (2/38)	
■ () <	
921 ⅔ 🖻 🖻 ·· ♦ anti anti 🕾 🗊 setup 😯 what would you like to setup?	Then with "done" the configuration will be saved. There is also the option to save this configuration to clone it in successive remote controls.
Samsung TV	
configurations store/load config	
done	

Г

CLONING PROCESS:

	Step 1: Access the settings screen
what would you like to setup? samsung TV configurations store/load config	Once the remote has successfully connected to the app, check if it supports cloning. If cloning is available, a button labeled Save/Load Settings will appear below the device information. Click the Save/Load Settings button. This will take you to the screen where the saved settings are listed, if available.
done	
store/load config	Step 2: Clone the remote control If no settings are saved, or if you want to create a new clone, tap the Clone Remote button at the bottom of the screen.
no saved configurations	
clone remote control	
back to the start	



	Step 3: Enter the name of the settings
store/load config	A dialog box will appear asking you to enter a name for the settings. Once the name is entered, press Save .
clone remote control	
clone remote control	
back to the start	
	Step 4: Save Settings
store/load config	Step 4: Save Settings It will take a few seconds for the app to clone itself and save the settings. After saving, the newly created configuration will appear in the list.
store/load config	Step 4: Save Settings It will take a few seconds for the app to clone itself and save the settings. After saving, the newly created configuration will appear in the list.
store/load config	Step 4: Save Settings It will take a few seconds for the app to clone itself and save the settings. After saving, the newly created configuration will appear in the list.
store/load config	Step 4: Save Settings It will take a few seconds for the app to clone itself and save the settings. After saving, the newly created configuration will appear in the list.
store/load config	Step 4: Save Settings It will take a few seconds for the app to clone itself and save the settings. After saving, the newly created configuration will appear in the list.
store/load config	Step 4: Save Settings It will take a few seconds for the app to clone itself and save the settings. After saving, the newly created configuration will appear in the list.
store/load config	Step 4: Save Settings It will take a few seconds for the app to clone itself and save the settings. After saving, the newly created configuration will appear in the list.
store/load config	Step 4: Save Settings It will take a few seconds for the app to clone itself and save the settings. After saving, the newly created configuration will appear in the list.
store/load config	Step 4: Save Settings It will take a few seconds for the app to clone itself and save the settings. After saving, the newly created configuration will appear in the list.
store/load config	Step 4: Save Settings It will take a few seconds for the app to clone itself and save the settings. After saving, the newly created configuration will appear in the list.



MANAGEMENT OF CLONED CONFIGURATIONS:

store/load config	Step 6: Load a Configuration To reload a saved configuration onto the remote control, tap the Load icon next to the configuration name.
store/load config clone1 V T rename clone1 cancel save	Step 7: Rename a Configuration If you need to rename a configuration, tap the pencil icon next to it. A dialog box will open where you can update the name by deleting the old one, entering the new name, and clicking Save .

ators/load config	Step 8: Delete a Configuration	
ne1	To delete a configuration, swipe left on the configuration name. A delete option will appear, allowing you to remove the saved configuration.	ć
clone remote control		
back to the start		

NOTE:

The procedure described above will configure the remote control unit with the codes of the selected TV. This way will be possible to control the TV via IR. Then the remote control unit, in its BT option, bluetooth, must be linked with the second device to be commanded: EK Cast (CRP 4K) or EK Hotel (STB Prof).

Pairing with CRP 4K:

(J) (E)	Tap the sequence:
	Back, Down, Up, Left, Right, OK with the original CPR 4K remote control.







STB Prof Linkage:





