

PIGTAIL KITS EK ROLLER - CPR Dca

**PFR 10 DT • PFR 15 DT • PFR 20 DT •
PFR 25 DT • PFR 30 DT • PFR 50 DT •
PFR 70 DT • PFR 100 DT**



**CPR
Dca**

- ✓ Fiber optic pigtails with 2 SC / APC anti-dust adapters and pigtail
- ✓ Different lengths available (10, 15, 20, 25, 30, 50, 70 and 100m)
- ✓ Pigtail with CPR Dca cover. External mounting ears, no need to open the rosette lid.
- ✓ Easy cable pull traction system



EKSELANS BY ITS

EK ROLLER

**PATENT
PENDING**

EK ROLLER is a new concept of cable dispenser patented by EK that presents unique advantages in the market. Its low weight and size allows it to be stored in the toolbox and it makes it very easy to use in any situation and environment. Thanks to its robust steel structure, supports both light reels of less than 1kg and reels of more than 30kg

- ✓ The quick fixing system to the fiber optic distribution kit boxes allows an easy and toolless swap in just two seconds
- ✓ EK ROLLER allows not only the unwinding of cable by simply pulling it, but also makes it easy the tedious task of winding the excess cable at the end of the installation
- ✓ The EK reels compatible with EK ROLLER also consist of an innovative system that prevents the excess cable from becoming entangled and guarantees a fluid unwinding of the same


EK ROLLER+ Includes a stabilizer accessory that adds weight to optimize the rotation of light coils or with little cable. The accessory has a optimized diameter for the range of PFR and PCR references, and it's also used on light coils compatible with **EK ROLLER**.




EK ROLLER+ with a special accessory for easy unwinding



Rosette detail with SC / APC adapters anti dust




Multiple possibilities for cable output



Detail of the traction system



Cardboard reel with EK ROLLER+ system



Mounting System for EK ROLLER+



Integrated holders on the reel



TECHNICAL TABLE

REFERENCE		PFR 10 DT	PFR 15 DT	PFR 20 DT	PFR 25 DT	PFR 30 DT	PFR 50 DT	PFR 70 DT	PFR 100 DT
Code		361111	361112	361113	361114	361115	361116	361117	361129
Capacity		2 fibras							
Fiber input		Side top corner							
Fiber type		Singlemode 900um G657-A2 LSZH Dca (green and red)							
Permanent traction	N	450							
Minimum bending radius	mm	18							
Adaptador		2 x SC / APC anti dust							
Fiber cable length	m	10	15	20	25	30	50	70	100
Dimensions (W x H x D)	mm	85 x 85 x 21							
Packaging	Uds	1 / 16							

REFERENCE	EK ROLLER +
Code	151062
Dimensions	15,5 x 15,5 x 1,4cm