

SPLITTERS



RQC 2M

- ✓ QuiCoax connection system
- ✓ 2 Outputs
- ✓ Low insertion loss
- ✓ DC pass
- ✓ MINI format



EKSELANS BY ITS



RQC 2M

01



Reduce to
minimum
installation time

02



**No need
of tools**

03



Guarantees
an **excellent
connected** and
minimizes the
space

04



Very high
shielding factor
CLASS A +10dB
throughout the
band

05



Eliminate the use
of **connectors**
and **associated
costs**

06



QuiCoax,
the new
**Standard of
Connection**



TECHNICAL TABLE

REFERENCE	RQC 2M
CODE	141009
LOSS	
Insertion loss (IN-OUT) 5-47 MHz	<3.5 dB
Insertion loss (IN-OUT) 47-950 Mhz	<4.0 dB
Insertion loss (IN-OUT) 950-2150 MHz	<5.5 dB
Insertion loss (IN-OUT) 2150-2400 Mhz	<6.0 dB
ISOLATION	
Isolation (OUT-OUT) 5-47 MHz	>35 dB
Isolation (OUT-OUT) 47-950 MHz	>30 dB
Isolation (OUT-OUT) 950-2150 MHz	>22 dB
Isolation (OUT-OUT) 2150-2400 MHz	>20 dB
RETURN LOSS	
Return loss 5-47 MHz	>15 dB
Return loss 47-950 MHz	>15 dB
Return loss 950-2150 MHz	>15 dB
Return loss 2150-2400 MHz	>12 dB
OPERATIONAL	
Impedance	75 Ω
Application	SAT, MATV 2.4Ghz +DC
Screening Efficiency	EN50083-2 Class A +10dB
DC Passthrough	Yes (max. 500mA)
Environment	Indoor
CONEXIÓN DEL CABLE	
Numero de entradas	1
Número de salidas	2
Tipo de conexión	QuiCoax
MECHANICAL	
Product Depth	16 mm
Product Height	32 mm
Product Width	61 mm
Packing QTY	1
Net Weight	0,081kg

Screening

100.0 kHz - 3.0 GHz Test length: 1.00m

