

SSW-2 Wireless Smart Plug User manual



Features

The smart plug is an accessory of smart alarm system. It is easy and reliable to use with elegant design. The smart plug could be controlled remotely by App.

Parameters

Reference	SSW-2
Code	261027
Rated Input	DC 220V-250V / 50-60 MHz / MAX 10A
Rated Output	AC 220V-250V/50-60Hz
Power Rating	2.500W
Transmission distance	Without obstacle 200m
Transmission frequency	433,92MHz
Working Temperature	-10°C ~ 40°C
Humidity	< 90% (non-condensing)
Dimension	102,0x62,5x29,7mm
Weight	159,5 gr (battery included)

Appearance



* We offer Smart Plug in global standards like CEE, GB, SAA, FC, etc. CEE standard is used for reference only in this document.

Pairing with Main Panel

Scanning the QR Code for Pairing.

- Scan the QR code printed on this accessory by App
- The APP will auto recognize smart plug, do NOT send out paring commands by APP
- now and just hold it
- Plug the smart plug on the socket or wall plug, press the LED button and LED will on
- 4 Send out the pairing commands by APP, the LED will off auto if pairing succeed.

Learn Mode (To GSM Alarm, if we doing Nova, please remove this part)

- Launch the PC client for turn on Learn Mode.
- Follow the guideline in App/PC client to trigger the accessory for the system to learn.
- The pairing result would be confirmed in App/PC client.

Hint: How to trigger?

- Plug it into the socket, light up the LED button.
- Hold the button for 10 seconds until it flashes.

Use The Smart Plug

1. Turn ON/OFF.

In the App , you could easily turn ON/OFF by tapping buttons in the Smart Plug section or in the main control panel.

2. Reset The Smart Switch

Keep holding the reset button in 10 seconds, the smart switch would be reset as the LED indicator keep flashing.



EKSELANS by ITS

ITS Partner O.B.S. S.L Av. Corts Catalanes 9-11 08173 Sant Cugat del Vallès Barcelona (Spain) Tel: +34 935839543