

SWD 8-20K - 334604



**Industrial Ethernet switch, 1 100BASE SC port  
+ 8 10/100/100BASE-T ports, SC fiber port,  
single mode, duplex fiber**

## DESCRIPTION

Industrial Ethernet switch, 1 100BASE SC port + 8 10/100/100BASE-T ports, SC fiber port, single mode, duplex fiber. Power supply not included



## KEY STRENGTHS

- 8 10/100Base-TX + 1 100Base-FX
- 10/100Mbps RJ45 Port Supports Full/Half-duplex, Auto-negotiation, Auto MDI/MDIX
- SFP, SC, FC, ST Optional
- Supports 802.3x Flow control
- IEEE 802.3az Energy Efficient Ethernet (EEE)
- Redundant Power Inputs
- Supports Wall-mount and DIN-Rail installation
- -40°C to 80°C (-40°F to 176°F) operating temperature



Updated on: 30 December 2025

This document is confidential and the property of ADALTRA. ADALTRA holds the copyright, and the document may not be copied or modified, in whole or in part, in any form, without ADALTRA's prior written permission. The features/specifications indicated in this document are non-contractual and may be changed without prior notice.

## SPECIFICATIONS

REFERENCE	SWD 8-20K
Code	334604
<b>ETHERNET</b>	
Standards	IEEE802.3 10BASE-T IEEE802.3u 100BASE-TX/FX IEEE802.3ab 1000BASE-T IEEE802.3z 1000BASE-X IEEE802.3x Flow Control IEEE 802.3az Energy Efficient Ethernet (EEE)
Forward & Filtering Rate	14,880pps (10Mbps) 148,800pps (100Mbps) 1,488,000pps (1000Mbps)
Packet Buffer Memory	512K bits
Processing Type	Store-and-Forward
Address Table Size	1024 MAC Addresses
<b>INTERFACE</b>	
Connector	8 x RJ45
Optical Port	1 x 1000Base-FX SC
<b>ENVIRONMENTAL</b>	
Operating Temperature	-40°C to 80°C (-40°F to 176°F)
Storage Temperature	-40°C to 85°C (-40°F to 185°F)
Relative Humidity	5% to 95% non-condensing
MTBF	> 200,000 hrs
<b>ELECTRICAL AND MECHANICAL</b>	
Input Power	12~58VDC, Redundant Power (6-pin Terminal Block)
Power Consumption	5W Max.
<b>PROTECTION</b>	
Power Input Overload	Automatic Resettable
Reverse Polarity	Present

## LED INDICATORS

Power	Power1, Power2 Status
Ethernet (Per Port)	Link/Activity
Fiber Port	FX1
Dimensions (WxDxH)	150 x 115 x 50 mm
Weight	0.6Kg
Casing	Metal Case
Mounting Options	DIN-Rail / Wall-mount