

SWG 16P-4SFP - 334404



Industrial L2+ PoE switch with 16 10/100/1000Base-T ports + 4 1000Base-X SFP ports

DESCRIPTION

Industrial L2+ PoE switch with 16 10/100/1000Base-T ports + 4 1000Base-X SFP ports. RJ45 ports 10/100/1000 Mbps (full/half duplex, auto-negotiation, Auto MDI/MDIX), IEEE 802.3af/at. DIP: VLAN, ring management, PoE reset, and PoE network up to 250m. Power supply not included.



KEY STRENGTHS

- Support 16x10/100/1000Base-T + 4x1000Base-X SFP +
- 10/100/1000Mbps RJ45 Port supports Full/Half-duplex, Auto-negotiation, Auto MDI/MDIX
- IEEE802.3af/at compliant
- DIP Switch supports one-key VLAN, one-key Ring Management, PoE Reset and 250m PoE Network
- Support connecting USB-C port for easy management, without the need to access the RS232 serial port at all
- 10K Bytes Jumbo Frame
- IEEE 802.3az Energy Efficient Ethernet (EEE)
- IP40 Aluminum Case
- Supports DIN-Rail installation
- -40°C to 80°C (-40°F to 176°F) operating temperature



Updated on: 30 October 2025

This document is confidential and the property of ADALTRA. ADALTRA holds the copyright, and the document may not be copied or modified, in whole or in part, in any form, without ADALTRA's prior written permission. The features/specifications indicated in this document are non-contractual and may be changed without prior notice.

SPECIFICATIONS

REFERENCE	SWG 16P-4SFP
Code	334404
ETHERNET	
Standards:	IEEE802.3 10BASE-T IEEE802.3u 100BASE-TX/FX IEEE802.3ab 1000BASE-T IEEE802.3z 1000BASE-X IEEE802.3p QoS IEEE802.1d Spanning Tree
Forward & Filtering Rate:	14,880pps (10Mbps) 148,800pps (100Mbps) 1,488,000pps (1000Mbps)
Packet Buffer Memory:	12M bits
Processing Type:	Store-and-Forward
Backplane bandwidth	110Gbps
Max Packet Length:	10K Bytes Jumbo Frame
Address Table Size:	8K MAC Addresses
INTERFACE	
Connector:	16 x RJ45
RS485:	1 x RS485 (Optional)
Optical Port:	4 x 1000Base-X SFP
USB-C:	1 x USB-C (for Management)
RS485 SERIAL INTERFACE (OPTIONAL)	
Physical interface	Industrial standard 3-pin screw terminal
Data type	1Ch RS485 Bi-Direction
RS-485 signals	Data+, Data-, GND
Serial port line	
distance (copper)	1000 meters
Baud rate	0 ~ 800kbps
PoE (POWER OVER ETHERNET)	
Standard:	IEEE 802.3at Power over Ethernet Plus IEEE 802.3af Power over Ethernet
Port:	RJ45
Power Pin Assignment	4/5(+), 7/8(-)
PoE Budget:	Up to 480-watt PoE budget

ENVIRONMENTAL

Operating Temperature:	-40°C to 80°C (-40°F to 176°F)
Storage Temperature:	-40°C to 85°C (-40°F to 185°F)
Relative Humidity:	5% to 95% non-condensing
MTBF	> 200,000 hrs

ELECTRICAL AND MECHANICAL

Input Power:	48~57VDC, Redundant Power (6-pin Terminal Block)
Power Consumption:	8W Max.(PoE in Use<480W)

PROTECTION:

Power Input Overload:	Automatic Resettable
Reverse Polarity:	Present

DIP SWITCH

4-digit DIP switch function 	DIP	FUNCTION	SETTINGS	
	SW 1	VLAN	ON - Enabled	OFF - Disabled
	SW 2	Ring Management	ON - Enabled	OFF - Disabled
	SW 3 (to be up-graded)	250m PoE Network	ON - Enabled	OFF - Disabled
	SW 4 (to be up-graded)	PoE Reset	ON - Enabled	OFF - Disabled

LED INDICATORS:

PWR:	Power Status
Ethernet (Per Port):	Link/Activity
PoE:	PoE Status
Fiber:	Gigabit SFP Port: F17~F20
Dimensions (WxDxH):	155 x 115 x 85 mm
Weight:	1.2Kg
Casing:	Aluminum Case
Mounting Options:	DIN-Rail mount

SOFTWARE FEATURES

Redundancy Protocols	Support STP/RSTP/MSTP/ERPSv2, Link Aggregation
Multicast Support	Support IGMP Snooping V1/V2/V3 support GMRP, GVMP, 802.1Q
VLAN	Support IEEE 802.1Q 4K VLAN support QinQ, Double VLAN,
Time Management	SNTP
QOS	Flow-based redirection Flow-based rate limiting Flow-based packet filtering 8*Output queues of each port 802.1p/DSCP priority mapping Diff-Serv QoS, Priority Mark/Remark Queue Scheduling Algorithm (SP, WRR, SP+WRR)
ACL	Port-based Issuing ACL ACL based on port and VLAN L2 to L4 packet filtering, matching first 80 bytes message. Provide ACL based on MAC, Destination MAC address, IP Source, Destination IP, IP Protocol Type, TCP/UDP Port, TCP/UDP Port Range, and VLAN, etc
PoE Management	Total power limit of PoE power supply PoE output power allocation PoE output priority configuration PoE working status Scheduling of PoE operation
Diagnostic Maintenance	Support port mirroring, Syslog, Ping
Management Function	Support CLI, WEB, SNMPv1/v2/v3, Telnet server for management, EEE, LLDP, DHCP Server/Client (IPv4/IPv6), Cloud/MQTT
Alarm Management	Support 1 way relay alarm output, RMON, TRAP
Security	Broadcast Storm Protection, HTTPS/SSLv3, AAA & RADIUS, SSH2.0 Support DHCP Snooping, Option 82, 802.1X security access, Support user hierarchical management, ACL access control list, Support DDOS, port-based MAC filtering / binding, MAC black holes, IP source protection, Port isolation, ARP message speed limit

Advance Layer 2+ Features	IPv4/IPv6 Management Static Route
REGULATORY APPROVALS	
ISO9001, CE, RoHS, FCC	
EN55022:2010+AC: 2011, Class A	
EN 61000-3-2: 2006+A1: 2009+A2: 2009	
EN 61000-3-3: 2013	
EN55024:2010	
IEC 61000-4-2: 2008 (ESD)	
IEC 61000-4-3: 2010 (RS)	
IEC 61000-4-4: 2012 (EFT)	
IEC 61000-4-5: 2014 (Surge)	
IEC 61000-4-6: 2013 (CS)	
IEC 61000-4-8: 2009 (PFMF)	