

Switches PoE

SWP 5 / SWP 9 / SWP 26

4 / 8 / 24 high-speed ethernet ports 10 / 100 / 1000

2 - 4 uplink ports (Ethernet and SFP Fiber 1GB)

PoE ports 48 Vdc

Total power 72W / 120W / 450W

Plug & Play

REFERENCE	SWP 5	SWP 9	SWP 26
Code	334001	334002	334003
PoE Power	72 W	120 W	450 W
PoE Standard	IEEE 802.3, 802.3u, 802.3x, 802.3af, 802.3at		
Ethernet Interface	4 x 10 / 100 / 1000 Mbps Ethernet ports 1 x 10 / 100 / 1000 Mbps Ethernet Uplink port 1 x 1000 SFP Fiber port	8 x 10 / 100 / 1000 Mbps Ethernet ports 1 x 10 / 100 / 1000 Mbps Ethernet Uplink port 1 x 1000 SFP Fiber port	24 x 10 / 100 / 1000 Mbps Ethernet ports 2 x 10 / 100 / 1000 Mbps Ethernet Uplink port 2 x 1000 SFP Fiber port
Back bandwidth	1 Gbps	1.8 Gbps	12.8 Gbps
MAC Address table	2000		8000
Power Supply	DC 48V / 1.5A Connector		100 - 240 V
Working temperature	0°C / 55°C		
Storage temperature	-40°C / 70°C		
Humidity	10% - 90%		
Size (L x W x H)	185 mm x 96 mm x 24 mm	250 mm x 122 mm x 35 mm	440 mm x 284 mm x 44 mm
Power consumption	Max. 72 W	Max. 120 W	Max. 450 W



SWP 5



SWP 9



SWP 26

Installation diagram:

